

定格表 (DB形標準品)

20150722EIG

項目 フレーム の大きさ	形 式	動作特性 記号	定格電圧	定格電流 (A)	定格遮断 電流 (kA)	オプション		過電流 引外し 方式
						防虫 カバー	補助 スイッチ	
30AF	DB21	A, B	AC110V	3, 5, 10 15, 20, 30	2.5	-	-	完全電磁式
			AC250V		1.0			
			DC125V		1.0			
	DB22	A, B	AC110V	3, 5, 10 15, 20, 30	2.5	-	-	
			AC250V		1.0			
			DC125V		1.0			
	DB23	A, B	AC110V	3, 5, 10 15, 20, 30	2.5	-	-	
			AC250V		1.0			
			DC125V		1.0			
30AF	DB31	A, B	AC300V	3, 5, 10 15, 20, 30	2.5	(○) 1P防虫標準	-	完全電磁式
			DC125V		2.5			
	DB32	A, B	AC300V	3, 5, 10 15, 20, 30	2.5	○	○	
			DC125V		2.5			
	C, D	AC460V	2.5	○	○			
		DC125V	2.5					
	DB33	A, B	AC300V	3, 5, 10 15, 20, 30	2.5	○	○	
			DC125V		2.5			
	C, D	AC460V	2.5					
50AF	DB51	A, B	AC300V	5, 10, 15, 20 30, 40, 50	2.5	-	-	完全電磁式
			DC125V		2.5			
	DB52	A, B	AC500V	5, 10, 15, 20 30, 40, 50	5.0	-	○	
			DC125V		5.0			
			DC250V		2.5			
	DB53	A, B	AC500V	5, 10, 15, 20 30, 40, 50	5.0	-	○	
			DC125V		5.0			
			DC250V		2.5			
	100AF	DB102	A, B	AC600V	15, 20, 30, 40 50, 60, 75, 100	10.0	-	
DC125V				10.0				
DC250V				10.0				
DB103		A, B	AC600V	15, 20, 30, 40 50, 60, 75, 100	10.0	-	○	
			DC125V		10.0			
			DC250V		10.0			
225AF	DB202	A, B	AC600V	125, 150, 175 200, 225	10.0	-	○	完全電磁式
			DC125V		10.0			
			DC250V		10.0			
	DB203	A, B	AC600V	125, 150, 175 200, 225	10.0	-	○	
			DC125V		10.0			
			DC250V		10.0			
400AF	DB402	A, B	AC600V	250, 300 350, 400	10.0	-	○	完全電磁式
			DC125V		10.0			
			DC250V		10.0			
	DB403	A, B	AC600V	250, 300 350, 400	10.0	-	○	
			DC125V		10.0			
			DC250V		10.0			

※: 詳細はカタログ参照